



Product Summary

NINA-W15 series

Stand-alone multiradio modules



Secure industrial multiradio made easy

- Simultaneous Wi-Fi 802.11 b/g/n and Bluetooth dual-mode
- Superior security functionality with built-in secure boot
- Feature rich, out-of-the-box connectivity software
- Small footprint and multiple antenna options
- Pin compatible with other NINA modules
- Global certification



10.0 × 10.6 × 2.2 mm



10.0 × 14.0 × 3.8 mm

Product description

The NINA-W15 series stand-alone multiradio modules integrate Wi-Fi, Bluetooth BR/EDR and Bluetooth low energy in a compact form factor. The NINA-W15 modules support simultaneous operation on Wi-Fi and Bluetooth dual-mode and can thus serve as a gateway between Bluetooth and Wi-Fi or Ethernet. They can act as both Wi-Fi station and micro access point and connect to a host system using either a UART or a high speed RMIII interface. Intended applications include telematics, industrial automation, connected buildings, wireless sensors, point-of-sales, and medical devices. The modules have many security features embedded, including secure boot, which ensures that only authenticated software is run on the module.

The NINA-W15 modules are used with u-blox connectivity software, which is pre-flashed at delivery. This significantly simplifies integration in the host system and speeds up the time to market. The software provides a number of features that can be configured from the host using AT commands. NINA-W15 modules are certified and approved for usage globally. They are qualified for professional grade operation, supporting an extended temperature range of -40 °C to +85 °C.

Product selector

Model	Radio	Interfaces	Features	Security	Grade
	Wi-Fi IEEE 802.11 version Wi-Fi output power EIRP [dBm] Maximum Wi-Fi range (m) Bluetooth BR/EDR and low energy v4.2 Bluetooth profiles Bluetooth BR/EDR output power EIRP [dBm] Bluetooth low energy output power EIRP [dBm] Maximum Bluetooth range (m) Antenna type	UART RMIII GPIO	Wi-Fi Station and Micro access point Throughput Bluetooth BR/EDR [Mbit/s] Throughput Bluetooth Low Energy [kbit/s] u-blox Low Energy Serial Port Service GATT server and GATT client Extended Data Mode protocol (EDM) TM Point-to-Point Protocol (PPP) AT command support Max simultaneous connections	WPA / WPA2 Enterprise security Secure boot	Standard Professional Automotive
NINA-W151	b/g/n 19 400 ● SG 9 9 200 P	● ● 13	● 1.0 200 ● ● ● ● ● ● 5	● ● ●	●
NINA-W152	b/g/n 19 300 ● SG 9 9 200 I	● ● 13	● 1.0 200 ● ● ● ● ● ● 5	● ● ●	●

P = antenna pin / I = internal antenna / S = SPP / G = GATT



NINA-W15 series



Features

Wi-Fi standards	802.11b/g/n 802.11d/e/i/h
Wi-Fi channels	2.4 GHz channels 1-13 (depending on the region)
Wi-Fi maximum transfer rates	802.11b: 11 Mbit/s 802.11g: 54 Mbit/s 802.11n: 72 Mbit/s
Wi-Fi output power	19 dBm EIRP
Wi-Fi Sensitivity (conducted)	-96 dBm conducted
Bluetooth output power	9 dBm EIRP (Bluetooth BR/EDR) 9 dBm EIRP (Bluetooth low energy)
Bluetooth sensitivity	-88 dBm conducted (Bluetooth BR/EDR 1 Mbit/s) -88 dBm conducted (Bluetooth low energy)
Antenna	Internal antenna or antenna pin for connecting to the external antenna

u-blox connectivity software

This section describes the NINA-W15 features integrated in the u-blox connectivity software. All NINA-W15 modules are delivered with this software and the module is configured using AT commands.

Wi-Fi features	Wi-Fi station Wi-Fi micro access point
Bluetooth features	SPP profile u-blox Low Energy Serial Port Service (SPS) GATT server and client Central and peripheral roles Up to 5 peripheral connections
Security features	WPA/WPA2 Enterprise security (EAP-TLS, PEAP) Secure boot Secure simple pairing
Extended Data Mode™	For individually controlled multipoint data channels
Point-to-Point Protocol	For UART-based IP connectivity between host and module, enables individually controlled data channels and AT commands in parallel
Configuration over air	Wireless transmission of AT commands to control the module
HW interfaces	UART, RMII, GPIO
Throughput	Bluetooth low energy 200 kbit/s Bluetooth BR/EDR 1 Mbit/s Wi-Fi 20 Mbit/s
Support tools	s-center

Interfaces

NINA-W151 and NINA-W152	UART, RMII, GPIO
-------------------------	------------------

Package

Dimensions	NINA-W151: 10.0 x 10.6 x 2.2 mm NINA-W152: 10.0 x 14.0 x 3.8 mm
Weight	< 1 g
Mounting	Machine mountable Solder pins

Environmental data, quality & reliability

Operating temperature	-40 °C to +85 °C
Storage temperature	-40 °C to +85 °C
Humidity	RH 5-90% non-condensing

Electrical data

Power supply	3.0 V to 3.6 V
Power consumption	Wi-Fi 15 dBm: 140 mA Bluetooth BR/EDR 6 dBm: 147 mA Bluetooth low energy 6 dBm: 57 mA Idle mode: 36 mA

Certifications and approvals

Type approvals	Europe (ETSI R&TTE), US (FCC/CFR 47 part 15 unlicensed modular transmitter approval), Canada (IC RSS), Japan (MIC), Taiwan (NCC), South Korea (KCC), Australia (ACMA) ¹ , New Zealand ¹ ; Brazil (Anatel) ¹ , South Africa (ICASA) ¹
Health and safety	EN 62479, EN 60950-1, IEC 60950-1
Medical Electrical Equipment	IEC 60601-1-2
Bluetooth qualification	v4.2 (Bluetooth BR/EDR and Bluetooth low energy)

¹ = Pending approvals

Support products

EVK-NINA-W151	Evaluation kit for NINA-W151 module with antenna pin and external antenna
EVK-NINA-W152	Evaluation kit for NINA-W152 module with internal antenna

Product variants

NINA-W151	With u-blox connectivity software and antenna pin
NINA-W152	With u-blox connectivity software and internal antenna

Further information

For contact information, see www.u-blox.com/contact-us.

For more product details and ordering information, see the [product data sheet](#).

Legal Notice:

u-blox reserves all rights to this document and the information contained herein. Products, names, logos and designs described herein may in whole or in part be subject to intellectual property rights. Reproduction, use, modification or disclosure to third parties of this document or any part thereof without the express permission of u-blox is strictly prohibited.

The information contained herein is provided "as is". No warranty of any kind, either express or implied, is made in relation to the accuracy, reliability, fitness for a particular purpose or content of this document. This document may be revised by u-blox at any time. For most recent documents, please visit www.u-blox.com.
Copyright © 2018, u-blox AG