


Product Summary

SARA-G450

Quad-band GSM/GPRS module



16.0 × 26.0 × 2.4 mm

Ideal for cost-optimized solutions

- Industry proven SARA form factor
- Easy migration between u-blox 2G, 3G, LPWA (Cat M1 and Cat NB1), LTE Cat 4 and LTE Cat 6 modules
- Simple integration with embedded Internet suite
- Optimized power consumption for IoT applications

Product description

The SARA-G450 GSM/GPRS module features class 12 GSM/GPRS connectivity in the popular u-blox SARA form factor.

The SARA-G450 module is an ideal solution for cost and space-sensitive applications. It offers an excellent price-to-performance ratio for all M2M applications where environmental conditions (temperature, EMC and mechanical stresses) are within standard levels.

Its rich feature set – including GSM/GPRS class 12 and simple integration – enable customers to easily integrate the module and develop a wide range of M2M devices.


Thanks to its pin compatibility with the u-blox modules SARA-G3 (GSM), SARA-U2 (HSPA), SARA-R4/N4 (LTE Cat M1/Cat NB1), SARA-N2 (LTE Cat NB1), TOBY-L2 (LTE Cat 4) and TOBY-R2/LARA-R2/LARA-R3121 (LTE Cat 1), the SARA-G450 allows customers to utilize the same PCB design, thus targeting various environmental requirements and different cellular technologies.

u-blox cellular modules are certified and approved by the main regulatory bodies and operators.

Product selector

Model	Data Rate	Bands	Positioning	Interfaces	Audio	Features	Grade
	GPRS multi-slot class 12 *	GSM/GPRS quad-band	Integrated GNSS receiver GNSS via modem AssistNow software CellLocate®	UART SPI USB 2.0 GPIO DDC for u-blox GNSS	Analog audio Digital audio	Network indication Antenna supervisor Jamming detection Embedded TCP/UDP Embedded FTP, HTTP Embedded SSL Dual stack IPv4/IPv6 FW update via serial interface	Standard Professional Automotive
SARA-G450	•	•	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	2(3) 4 <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	• • <input type="checkbox"/> • • • • •	•

* = Downgradeable to class 10 via AT command / = Available in future FW version / (3) = Third UART supported in future FW versions



Features

GSM	GSM 850/900/1800/1900 MHz 3GPP Release 99
GPRS	GPRS Class 12 (downgradeable to Class 10 with AT command) CS1-CS4 - up to 85.6 kbit/s PBCCH support
AT Commands	3GPP TS 27.005, 3GPP TS 27.007 u-blox AT command extension 3GPP 27.010 MUX protocol
SMS	MT/MO Text/PDU mode
Firmware upgrade	Via UART
Voice ¹	Codec: HR / FR / EFR / AMR
Protocols	Embedded TCP/IP, UDP/IP, HTTP, FTP, SSL and TLS 1.2 support
GNSS Interfaces ¹	Direct access to u-blox GNSS via module CellLocate® & Hybrid Positioning
Special features	Bearer Independent Protocol (BIP) ¹ IPv6 support over PPP

Electrical data

Power supply	3.40 V to 4.20 V	
Digital I/O voltage level	1.8 V / 2.8 V to 3.0 V (selectable)	
Power consumption	Power Off:	< 100 µA
	Idle mode:	< 1.5 mA
	Connected:	< 230 mA

Interfaces

Antenna	50 Ω SMT pad
Serial Port	1 UART for data and AT commands 1 UART for FW upgrade and tracing
SIM	1.8 V and 3.0 V
GPIO	4, controllable over AT commands
GNSS serial ¹	1 DDC (I ² C)
Audio ¹	1 analog 1 digital (I ² S/PCM)

¹ = in future FW versions

Further information

For contact information, see www.u-blox.com/contact-us.

For more product details and ordering information, see the [product data sheet](#).

Package

96 pin LGA: 16.0 x 26.0 x 2.4 mm, < 3 g

Environmental data, quality & reliability

Operating range -20 °C to +70 °C

Extended range -40 °C to +75 °C

RoHS compliant (lead-free)

Certifications and approvals

SARA-G450 modules offer a comprehensive set of regulatory certifications and approvals, including RED, ICASA, SRRC/CCC, GCF, and Anatel.

Contact your closest u-blox representative for the latest approvals.

Support products

EVK-G45 Evaluation Kit for SARA-G450

Product variants

SARA-G450 Quad-band GSM/GPRS module

Legal Notice:

u-blox reserves all rights to this document and the information contained herein. Products, names, logos and designs described herein may in whole or in part be subject to intellectual property rights. Reproduction, use, modification or disclosure to third parties of this document or any part thereof without the express permission of u-blox is strictly prohibited.

The information contained herein is provided "as is". No warranty of any kind, either express or implied, is made in relation to the accuracy, reliability, fitness for a particular purpose or content of this document. This document may be revised by u-blox at any time. For most recent documents, please visit www.u-blox.com.
Copyright © 2018, u-blox AG