

# ZED-F9H




## u-blox F9 high precision GNSS module

### u-blox F9 module designed for heading applications

- Precise heading information to all types of vehicles
- Suitable for UAV, trucks, heavy vehicles and antenna alignment applications
- Heading accuracy independent of vehicle motion and calibration



17.0 × 22.0 × 2.4 mm



### Product description

The ZED-F9H module is designed to provide best possible heading information to applications where precise attitude is of greatest importance.

The ZED-F9H acts as an accompanying module, and requires a ZED-F9P module to be mounted on the same vehicle. In this setup, ZED-F9P provides the precise GNSS position, and at the same time acts as a moving base to the ZED-F9H module, which in turn outputs the precise attitude information.

As the heading information is based on GNSS it does not require pre-calibration, thus ensuring easy production, integration and operation. The precise heading information is always available, even in stand-still situations.

ZED-F9H is designed to lower the system cost for a heading application and comes with minimal e-BOM. It is well-suited for mass market adoption, thanks to its small package size, light weight, and low power consumption.

u-blox modules are manufactured in ISO/TS 16949 certified sites and are fully tested on a system level. Qualification tests are performed as stipulated in the ISO16750 standard: "Road vehicles – Environmental conditions and testing for electrical and electronic equipment".

ZED-F9H

Grade	
Automotive	
Professional	•
Standard	
GNSS	
GPS / QZSS	•
GLONASS	•
Galileo	•
BeiDou	•
Number of concurrent GNSS	4
Multi-band	•
Interfaces	
UART	2
USB	1
SPI	1
DDC (I <sup>2</sup> C compliant)	1
Features	
Programmable (Flash)	•
Data logging	•
Carrier phase output	
Additional SAW	•
RTC crystal	•
Oscillator	T
RTK rover	
RTK base station	
Timepulse	1
Power supply	
2.7 V – 3.6 V	•

T = TCXO



## Features

Receiver type	184-channel u-blox F9 engine GPS L1C/A L2C, GLO L1OF L2OF, GAL E1B/C E5b, BDS B1I B2I, QZSS L1C/A L2C	
Heading accuracy <sup>1</sup>	0.4 degrees	
Heading update rate <sup>2</sup>	up to 10 Hz	
Acquisition	Cold starts	24 s
	Aided starts	2 s
	Reacquisition	2 s
Sensitivity	Tracking & Nav.	-167 dBm
	Cold starts	-148 dBm
	Hot starts	-157 dBm
	Reacquisition	-160 dBm
Oscillator	TCXO	
RTC crystal	Built-In	
Anti-jamming	Active CW detection and removal Onboard band pass filter	
Anti-spoofing	Advanced anti-spoofing algorithms	
Memory	Flash	
Supported antennas	Active	

1 50%, measured with 1 m baseline and patch antennas with good ground planes  
2 The highest navigation rate can limit the number of supported constellations

## Interfaces

Serial interfaces	2 UART	
	1 SPI	
	1 USB	
	1 DDC (I <sup>2</sup> C compliant)	
Digital I/O	Configurable timepulse EXTINT input for wakeup RTK fix status	
Timepulse	Configurable: 0.25 Hz to 10 MHz	
Protocols	NMEA, UBX binary, RTCM version 3.3	

## Further information

For contact information, see [www.u-blox.com/contact-us](http://www.u-blox.com/contact-us).

For more product details and ordering information, see the [product data sheet](#).

## Package

54-pin LGA (Land Grid Array)  
17 x 22 x 2.4 mm

## Environmental data, quality & reliability

Operating temp. -40 °C to +85 °C

Storage temp. -40 °C to +85 °C

RoHS compliant (2015/863/EU)

Green (halogen-free)

EU Radio Equipment Directive compliant 2014/53/EU

Qualification according to ISO 16750

Manufactured and fully tested in ISO/TS 16949 certified production sites

High vibration and shock resistance

## Electrical data

Supply voltage 2.7 V to 3.6 V

Power consumption 68 mA @ 3.0 V (continuous)

Backup supply 1.65 V to 3.6 V

## Support products

u-blox support products provide reference design, and allow efficient integration and evaluation of u-blox positioning technology.

C099-F9P u-blox ZED-F9P application board, with ODIN-W2 for connectivity. Includes multi-band antenna (ANN-MB). One board per package. See product documentation for more details.

## Product variants

ZED-F9H u-blox F9 precision heading GNSS module

## Legal Notice:

u-blox reserves all rights to this document and the information contained herein. Products, names, logos and designs described herein may in whole or in part be subject to intellectual property rights. Reproduction, use, modification or disclosure to third parties of this document or any part thereof without the express permission of u-blox is strictly prohibited.

The information contained herein is provided "as is". No warranty of any kind, either express or implied, is made in relation to the accuracy, reliability, fitness for a particular purpose or content of this document. This document may be revised by u-blox at any time. For most recent documents, please visit [www.u-blox.com](http://www.u-blox.com).  
Copyright © 2019, u-blox AG