

Product Summary

ZED-F9T




u-blox F9 high accuracy timing module



Multi-band GNSS receiver with nanosecond-level timing accuracy

- Meets the most stringent 5G timing requirements
- Ideal for global deployments due to GPS, BeiDou, Galileo, and GLONASS reception
- Unaffected by ionospheric errors
- Differential timing mode for highly accurate local timing
- Built-in security for highest robustness against malicious attacks



17.0 × 22.0 × 2.4 mm

Product description

The ZED-F9T timing module provides nanosecond-level timing accuracy to the most demanding infrastructure applications.

ZED-F9T is designed to meet the most stringent timing synchronization requirements in 5G mobile networks on a global scale. By significantly reducing the time error of the primary source of cellular network synchronization, the ZED-F9T will help operators maximize the performance of their networks and so optimize the return on their investment in 5G communications.

The timing module's multi-band capability reduces the timing error under clear skies to less than 5 ns without the need for an external GNSS correction service. To further improve accuracy locally, the ZED-F9T features differential timing modes that exchange correction data with other neighboring GNSS timing receivers via a communication network.

Multi-band access to all four satellite constellations strengthens the receiver's capability for delivering more reliable performance.

ZED-F9T includes advanced security features such as secure boot, secure interfaces, and T-RAIM to provide the highest level timing integrity.

The module has a single RF input for all the GNSS bands and dual SAW filters for exceptional signal selectivity and out-of-band attenuation.

u-blox modules use GNSS chips qualified according to AEC-Q100, are manufactured in ISO/TS 16949 certified sites, and are fully tested on a system level. Qualification tests are performed as stipulated in the ISO16750 standard: "Road vehicles – Environmental conditions and testing for electrical and electronic equipment".

Product selector

Model	Category	GNSS	Supply	Interfaces	Features	Grade	
	Standard Precision GNSS High Precision GNSS Dead Reckoning Timing	GPS/QZSS GLONASS Galileo BeiDou	Number of concurrent GNSS Multi-band	2.7 V – 3.6 V	USB UART SPI DDC (I ² C compliant)	Programmable (flash) Additional SAW Carrier phase output Internal TXCO oscillator Timepulse output Time-mark input	Standard Professional Automotive
ZED-F9T	•	• • • •	4 •	• • • •	• • • • •	•	





Features

Receiver type	184-channel u-blox F9 engine GPS L1C/A L2C, GLO L1OF L2OF, GAL E1B/C E5b, BDS B1I B2I, QZSS L1C/A L2C SBAS L1C/A: WAAS, EGNOS, MSAS, GAGAN	
Nav. update rate ¹	up to 20 Hz	
Position accuracy ²	Standalone	2.0 m CEP
Acquisition	Cold starts	26 s
	Aided starts	2 s
	Reacquisition	1 s
Tracking & Nav.	-166 dBm	
Reacquisition	-160 dBm	
Hot starts	-156 dBm	
Cold starts	-148 dBm	
Assistance	AssistNow Online OMA SUPL & 3GPP compliant	
Oscillator	TCXO	
RTC crystal	Built-In	
Anti-jamming	Active CW detection and removal Dual onboard band pass filters	
Anti-spoofing	Advanced anti-spoofing algorithms	
Security	Secure boot	
	Secure firmware update	
Memory	Flash	
Supported antennas	Active	

- 1 The highest navigation rate can limit the number of supported constellations
2 Depends on atmospheric conditions, baseline length, GNSS antenna, multipath conditions, satellite visibility, and geometry

Features - Timing

Timing accuracy	<5 ns (1-sigma, clear sky, absolute mode)
	<2.5 ns (1-sigma, clear sky, differential mode)
Timepulse frequency	0.25Hz – 30 MHz
Timepulse jitter	±4 ns
Time-mark resolution	8 ns
Integrity reports	T-RAIM active, phase uncertainty
	Time-pulse rate/duty-cycle, inter-constellation biases
Survey-in period	Configurable

Features - Raw data

Measurement data	Carrier phase, code phase & pseudo-range, Doppler on all signals
Message data	GPS, GLONASS, BeiDou, Galileo, QZSS, SBAS

Further information

For contact information, see www.u-blox.com/contact-us.

For more product details and ordering information, see the [product data sheet](#).

Package

54-pin LGA (Land Grid Array)
17.0 x 22.0 x 2.4 mm

Environmental data, quality & reliability

Operating temp.	-40 °C to +85 °C
Storage temp.	-40 °C to +85 °C
RoHS compliant (lead-free)	
Green (halogen-free)	
ETSI-RED compliant	
Qualification according to ISO 16750	
Manufactured and fully tested in ISO/TS 16949 certified production sites	
Uses u-blox F9 chips qualified according to AEC-Q100	
High vibration and shock resistance	

Electrical data

Supply voltage	2.7 V to 3.6 V
Power consumption	68 mA @ 3.0 V (continuous)
Backup supply	1.65 V to 3.6 V

Interfaces

Serial interfaces	1 USB
	1 UART
	1 SPI
	1 DDC (I ² C compliant)
Protocols	NMEA, UBX binary, RTCM version 3.3
Timepulse outputs	2
Time-mark outputs	2

Support products

u-blox support products provide reference design, and allow efficient integration and evaluation of u-blox positioning technology.

RCB-F9T	u-blox F9 multi-band GNSS timing board
ANN-MB	Multi-band active GNSS antenna

Product variants

ZED-F9T	u-blox F9 high accuracy timing module
---------	---------------------------------------

Legal Notice:

u-blox reserves all rights to this document and the information contained herein. Products, names, logos and designs described herein may in whole or in part be subject to intellectual property rights. Reproduction, use, modification or disclosure to third parties of this document or any part thereof without the express permission of u-blox is strictly prohibited.

The information contained herein is provided "as is". No warranty of any kind, either express or implied, is made in relation to the accuracy, reliability, fitness for a particular purpose or content of this document. This document may be revised by u-blox at any time. For most recent documents, please visit www.u-blox.com.
Copyright © 2018, u-blox AG