


MAYA-W3 series



Host-based Wi-Fi 6/6E and Bluetooth® 5.4 modules for the IoT

Small, low-power, secure modules for IoT applications

- Single-band, dual-band, and tri-band Wi-Fi 6/6E
- Dual-mode Bluetooth Classic and Bluetooth Low Energy 5.4
- Bluetooth LE Audio
- Efficient coexistence management between internal and external radios
- Variants with PCB-antenna, U.FL connector(s), and antenna pins
- Secure boot and secure OTP



Product description

The MAYA-W3 series host-based modules are designed, built, and tested to meet the high reliability and quality requirements of a wide range of industrial applications, such as smart manufacturing, tracking and telematics, building automation, professional appliances, healthcare, and EV charging infrastructures.

MAYA-W3 modules provide SISO Wi-Fi 6/6E operation with 20 MHz channel width, improved network availability in dense Wi-Fi environments, and MU-MIMO. The modules can work as access point, station, in P2P connections, or combinations of these. MAYA-W3 supports Bluetooth Low Energy 5.4, including the use of isochronous channels for LE Audio.

At 10.4 x 14.3 mm, MAYA-W3 are among the most compact Wi-Fi 6/6E SMD modules available in the market.

All u-blox modules undergo extensive qualification tests to ensure reliability over their life-time, and each module is fully tested before leaving the assembly line.

The MAYA-W3 series is based on the CYW5551/2/3 chips from Infineon.

Key features

- Variants with antenna pins, U.FL connectors, and embedded PCB antenna
- Wi-Fi 6/6E, tri-band, dual-band, and single-band; single stream, supporting MU-MIMO
- 20 MHz Wi-Fi channels
- Wi-Fi 802.11a/b/g/n/ac/ax/ - d/e/h/i/r/w
- Bluetooth 5.4 supporting LE Audio
- Wi-Fi security: WPA3, WPA2, WAPI, AES
- High-power Bluetooth: up to +20 dBm
- Secure boot
- Industrial temperature range -40 °C to +85 °C

MAYA-W330
MAYA-W331
MAYA-W336
MAYA-W360
MAYA-W361
MAYA-W366
MAYA-W380
MAYA-W381
MAYA-W386

	MAYA-W330	MAYA-W331	MAYA-W336	MAYA-W360	MAYA-W361	MAYA-W366	MAYA-W380	MAYA-W381	MAYA-W386
Grade									
Automotive									
Professional		•		•				•	
Standard									
Radio									
Chip inside	CYW55511			CYW55512			CYW55513		
Bluetooth qualification	v5.4			v5.4			v5.4		
Bluetooth profiles	HCI			HCI			HCI		
Bluetooth Classic	•			•			•		
Bluetooth Low Energy	•			•			•		
Bluetooth output power conducted [dBm]	up to 20			up to 20			up to 20		
Wi-Fi IEEE 802.11 stds	Wi-Fi 6 (802.11a/b/g/n/ac/ax)								
Wi-Fi freq. band [GHz]	2.4			2.4 and 5			2.4, 5, and 6		
Wi-Fi output power [dBm]	18			18			18		
Antenna type	U.FL pins pcb			U.FL pins pcb			U.FL pins pcb		
Number of antennas	2	2	1	2	2	1	2	2	1
OS support									
Android / Linux drivers	•			•			•		
RTOS (via NXP MCU)	•			•			•		
Interfaces									
High-speed UART (Bluetooth)	1			1			1		
PCM, I2S (Bluetooth audio)	1			1			1		
SDIO (Wi-Fi) [version]	3.0			3.0			3.0		
Features									
Micro access points [max]	16			16			16		
Wi-Fi direct	•			•			•		
WPA3	•			•			•		
RF calibration in OTP	•			•			•		
Programmed MAC addr.	•			•			•		
Secure boot	•			•			•		

pins = 2 antenna pins
pcb = internal PCB antenna and pin

U.FL = 2 U.FL antenna connectors



Features

Wi-Fi standards	Wi-Fi 6/E IEEE 802.11a/b/g/n/ac/ax IEEE 802.11d/e/h/i/r/w
Wi-Fi channels	2.4 GHz: 1-14 5 GHz: 36-196 6 GHz: 1-233
Bluetooth	v5.4 Classic and LE long range, power management, LE Audio
Antennas	MAYA-W330, MAYA-W360 and MAYA-W380: 2 U.FL connectors MAYA-W331, MAYA-W361 and MAYA-W381: 2 antenna pins MAYA-W336, MAYA-W366 and MAYA-W386: 1 antenna via pin or embedded in PCB
Wi-Fi output Tx-power	18 dBm (Wi-Fi 6, 5 GHz, 20 MHz channel)
RX sensitivity	Wi-Fi 6 2.4 GHz: -95 dBm (indicative) Wi-Fi 6 5 GHz: -94 dBm (indicative) Bluetooth Classic: -94 dBm (indicative) Bluetooth LE: -100.5 dBm (1 Mbit/s, indicative)
Security	128-bit AES hardware encryption Secure boot

Software features

RF calibration	Available in on-board OTP memory
MAC addresses	Available in on-board OTP memory
Security	WPA2 (CCMP, AES) WPA3 WAPI
Wi-Fi operational modes	Station, access point, Wi-Fi direct, or any combination of these
Driver support	Free of charge drivers for Linux and Android
Wi-Fi/Bluetooth coexistence	Internal TDM mechanism Central hardware packet traffic arbitration for external radio WCI-2 interface for external radio coexistence

Interfaces

Wi-Fi	SDIO 3.0 (4-bit, up to 100 MHz clock)
Bluetooth	4-wire high-speed UART PCM and I2S for Bluetooth audio
Coexistence	WCI-2 (2-wire) Zigbee (3-wire) UWB (3-wire) 4-wire LTE
Other	GPIOs

Package

Dimensions	10.4 × 14.3 × 1.9 mm
Mounting	Soldering, 90 pins (LGA)

Environmental data, quality, and reliability

Operating temperature	-40 °C to +85 °C
Moisture sensitivity level	4
RoHS and REACH compliance	

Electrical data

RF power supply	3.13 – 3.46 VDC
I/O power supply	3.3 VDC or 1.8 VDC

Certifications and approvals

Type approvals	Europe (RED); US (FCC); Canada (ISED); Japan (Giteki) Other certifications to be considered upon request
Bluetooth qualification	v5.4 (Bluetooth Classic and Bluetooth Low Energy)

Support products

EVK-MAYA-W381	Evaluation kit for all MAYA-W3 modules
---------------	--

Product variants

MAYA-W330	Single-band Wi-Fi 6 and Bluetooth 5.4 module with two separate U.FL connectors
MAYA-W331	Single-band Wi-Fi 6 and Bluetooth 5.4 module with two separate antenna pins
MAYA-W336	Single-band Wi-Fi 6 and Bluetooth 5.4 module with embedded PCB antenna
MAYA-W360	Dual-band Wi-Fi 6 and Bluetooth 5.4 module with two separate U.FL connectors
MAYA-W361	Dual-band Wi-Fi 6 and Bluetooth 5.4 module with two separate antenna pins
MAYA-W366	Dual-band Wi-Fi 6 and Bluetooth 5.4 module with embedded PCB antenna
MAYA-W380	Tri-band Wi-Fi 6E and Bluetooth 5.4 module with two separate U.FL connectors
MAYA-W381	Tri-band Wi-Fi 6E and Bluetooth 5.4 module with two separate antenna pins
MAYA-W386	Tri-band Wi-Fi 6E and Bluetooth 5.4 module with embedded PCB antenna

Further information

For contact information, see www.u-blox.com/contact-u-blox.

For more product details and ordering information, see the [product data sheet](#).

Legal Notice:

u-blox or third parties may hold intellectual property rights in the products, names, logos and designs included in this document. Copying, reproduction, or modification of this document or any part thereof is only permitted with the express written permission of u-blox. Disclosure to third parties is permitted for clearly public documents only.

The information contained herein is provided "as is". No warranty of any kind, either express or implied, is made in relation to the accuracy, reliability, fitness for a particular purpose or content of this document. This document may be revised by u-blox at any time. For most recent documents, please visit www.u-blox.com.