

# NORA-W45 series



## Stand-alone Wi-Fi 6 multiradio modules

### Single-band Wi-Fi 6 network processor

- Single-band Wi-Fi 6 and Bluetooth Low Energy 5.3
- u-connectXpress for accelerated time to market
- Wide range of embedded security features
- Small footprint, multiple antenna options, pin compatible with other NORA modules
- Global certification



10.4 x 14.3 x 1.9 mm



### Product description

NORA-W45 series are small, stand-alone, single-band Wi-Fi 6 and Bluetooth Low Energy wireless modules, with everything needed for integration into end-products. The modules are ideal for users looking to add advanced wireless connectivity to their end products.

With Wi-Fi 6, several features improve network efficiency, latency, range, and power consumption compared to earlier Wi-Fi generations. In addition, Bluetooth Low Energy 5.3 further expands the number of use cases supported.

The modules are delivered with u-connectXpress software for simple end-product integration and reduced time-to market. The host controller configures the wireless communication using high-level AT commands with no need for expertise in Wi-Fi and Bluetooth protocol stacks. NORA-W45 supports Wi-Fi station or access point mode, and can take both roles concurrently. It can take Bluetooth peripheral and central roles, or both simultaneously. It can be a GATT client and server. NORA-W45 supports Bluetooth LE connections both in high data rate mode (2 Mbit/s PHY) and long range mode (125 kbit/s coded PHY). The software comes with a TCP/IP stack allowing for point-to-point and point-to-multipoint use cases.

For secure communication with cloud-based applications and services, support for TLS encryption and MQTT protocols is provided. NORA-W45 has secure authentication methods like WPA/WPA3, Wi-Fi enterprise security, and Bluetooth LE secure connections. A wide range of other features are also supported, all accessible through the AT command interface.

NORA-W456's internal PCB antenna provides a robust, low-profile solution and an extensive range, while NORA-W451 has a module pin to connect to an external antenna of choice. The modules are globally certified for use with the internal antenna or a range of external antennas. This reduces time, cost and effort for customers integrating Wi-Fi and Bluetooth Low Energy in their products.

The modules are ideally suited to a wide range of applications, including industrial automation, smart buildings and homes, smart city, healthcare and medical devices, and telematics.

	NORA-W451	NORA-W456
<b>Grade</b>		
Automotive		
Professional	•	•
Standard		
<b>Radio</b>		
Chip inside	ESP32-C6	ESP32-C6
Bluetooth qualification	v5.3	v5.3
Bluetooth Low Energy	•	•
Bluetooth output power EIRP [dBm]	TBD	TBD
Wi-Fi bands [GHz]	2.4	2.4
Wi-Fi IEEE 802.11 standards	a/b/g/n/ax	a/b/g/n/ax
Wi-Fi output power EIRP [dBm]	TBD	TBD
Antenna type (see footnotes)	pin	pcb
<b>Application software</b>		
u-connectXpress	•	•
<b>Interfaces</b>		
UART	•	•
GPIO pins (user available)	TBD	TBD
<b>Features</b>		
AT command interface	•	•
Access point	•	•
TCP/IP stack	•	•
MQTT client	•	•
Wi-Fi throughput [Mbit/s]	TBD	TBD
WPA2/WPA3	•	•
Wi-Fi enterprise security	•	•
End-to-end security (TLS)	•	•
Maximum Bluetooth connections	TBD	TBD
Low Energy Serial Port Service	•	•
Secure boot	•	•

pin = Antenna pin  
pcb = Internal PCB antenna



## Features

Wi-Fi standards	IEEE 802.11 a/b/g/n/ax
Wi-Fi channels	2.4 GHz channels 1-13 (depending on region)
Wi-Fi maximum transfer rates	IEEE 802.11 a/g: 54 Mbit/s IEEE 802.11 b: 11 Mbit/s IEEE 802.11 n: 72 Mbit/s IEEE 802.11 ax: 115 Mbit/s
Bluetooth	v5.3 Bluetooth Low Energy
Bluetooth PHY rate	125 kbps, 1 Mbps, 2 Mbps
Output power (conducted)	Wi-Fi 2.4 GHz: TBD Bluetooth: TBD
Sensitivity	Wi-Fi 2.4 GHz: TBD Bluetooth: TBD
Antenna	Internal PCB antenna or antenna pin for connecting to an external antenna

## Electrical data

Power supply	3.3 V (+/-10%)
Power consumption	TBD

## u-connectXpress features

This section describes the NORA-W45 features integrated in the u-connectXpress software. All modules are delivered with this software pre-flashed and configured using AT commands.

Wi-Fi features	Wi-Fi station Wi-Fi access point
Bluetooth features	u-blox Low Energy Serial Port Service (SPS) GATT server and client Simultaneous central and peripheral roles
Security features	Secure boot WPA2/WPA3 Enterprise security (EAP-TLS, PEAP) End-to-end security with TLS 1.2/1.3 Protected Management Frames (PMF) Secure Simple Pairing Bluetooth LE secure connections
IoT features	TCP/UDP client/server MQTT client HTTP client DHCP client/server
Throughput (user data)	Bluetooth Low Energy: TBD Wi-Fi: TBD
Support tools	s-center

## Further information

For contact information, see [www.u-blox.com/contact-u-blox](http://www.u-blox.com/contact-u-blox).

For more product details and ordering information, see the [product data sheet](#).

## Package

Dimensions	10.4 x 14.3 x 1.9 mm
Mounting	Machine mountable solder pins

## Environmental data, quality & reliability

Operating temperature	-40 °C to +85 °C
Storage temperature	-55 °C to +125 °C
Humidity	RH 5-90% non-condensing
RoHS directive	RoHS 2 and RoHS 3

## Certifications and approvals<sup>1</sup>

Type approvals	Europe (RED), Great Britain (UKCA), US (FCC), Canada (ISED), Japan (MIC), Taiwan (NCC), South Korea (KCC), Australia (ACMA), New Zealand
Health and safety	EN 62479, EN 62368-1, IEC 62311
Medical Electrical Equipment	IEC 60601-1-2
Bluetooth qualification	Bluetooth Low Energy 5.3, qualification pending

<sup>1</sup> = Certifications are pending

## Support products

EVK-NORA-W451	Evaluation kit for NORA-W451 module with antenna pin
EVK-NORA-W456	Evaluation kit for NORA-W456 module with internal PCB antenna

## Product variants

NORA-W451	Multiradio module with u-connectXpress and antenna pin
NORA-W456	Multiradio module with u-connectXpress and internal PCB antenna

## Legal Notice:

u-blox or third parties may hold intellectual property rights in the products, names, logos and designs included in this document. Copying, reproduction, or modification of this document or any part thereof is only permitted with the express written permission of u-blox. Disclosure to third parties is permitted for clearly public documents only.

The information contained herein is provided "as is". No warranty of any kind, either express or implied, is made in relation to the accuracy, reliability, fitness for a particular purpose, or content of this document. This document may be revised by u-blox at any time. For most recent documents, please visit [www.u-blox.com](http://www.u-blox.com).