

# UBX-G6010-NT

## Smallest ever u-blox 6 GPS chip

### Highlights

- High performance GPS engine
- Minimal space (less than 7 x 8 mm PCB area)
- High level of design flexibility
- eBoM requires as few as 5 components
- Capture & Process support



UBX-G6010-NT:  
5.0 x 6.0 x 1.1 mm

### Features

- u-blox 6 position engine:
  - Navigate down to -162 dBm and -148 dBm coldstart
  - Faster acquisition with AssistNow Autonomous
  - Configurable power management
  - Hybrid GPS/SBAS engine (WAAS, EGNOS, MSAS)
  - Anti-jamming technology
- Simple integration with u-blox wireless modules
- A-GPS: AssistNow Online and AssistNow Offline services, OMA SUPL compliant
- Supports ultra-low power logging and geo-tagging applications with Capture & Process technology<sup>1</sup>
- Operating temperature range: -40°C to 85°C
- 3GPP compliant
- Compatible with u-blox GPS Solution for Android

<sup>1</sup> Requires u-blox' YUMA, available separately.

### Product description

The UBX-G6010-NT is u-blox' smallest ever GPS chip featuring the high performance u-blox 6 position engine. Sophisticated interference suppression ensures maximum performance even in GPS-hostile environments. By integrating most passive components, the UBX-G6010-NT reduces the eBoM and minimizes space requirements for GPS solutions to less than 7 x 8 mm.

u-blox 6 has been designed with low power consumption in mind, with intelligent power management enabling low-power applications. The minimal eBoM requires as few as 5 components (including SAW filter and TCXO). Both LDO and LNA are integrated, and costly external memory is not needed. Lower price GPS crystals as well as TCXOs are supported, 2-layer PCB integration capability and small footprint ensure further cost savings.

The UBX-G6010-NT is the ideal solution for space sensitive applications requiring flexible performance and cost options.

### Product selector

Model	Type	Supply	Interfaces	Features
	Standalone GPS Capture & Process Timing & Raw Data Dead Reckoning	1.75 V – 2.0 V 2.5 V – 3.6 V	UART USB SPI DDC (I <sup>2</sup> C compliant)	Programmable (Flash) FW update Oscillator RTC crystal Antenna supply and supervisor Configuration pins Timepulse External interrupt / Wakeup
UBX-G6010-NT	• Y	• •	• • • •	C/T ○ ○ 10 2 2

Y = requires u-blox' YUMA (available separately)  
C/T = Crystal and TCXO supported

○ = requires external components

## Receiver performance data

Receiver type	50-channel u-blox6 engine GPS L1 C/A code SBAS: WAAS, EGNOS, MSAS		
Navigation update rate	up to 5 Hz		
Accuracy <sup>1</sup>	Position	2.5 m CEP	
	SBAS	2.0 m CEP	
Acquisition <sup>1</sup>		TCXO	Crystal
	Cold starts:	26 s	27 s
	Aided starts <sup>2</sup> :	1 s	< 3 s
	Hot starts:	1 s	1 s
Sensitivity <sup>3</sup>		TCXO	Crystal
	Tracking:	-162 dBm	-161 dBm
	Cold starts:	-148 dBm	-147 dBm
	Hot starts:	-157 dBm	-156 dBm
Operational limits	Velocity:	500 m/s	
	Altitude:	50,000 m	

<sup>1</sup> All SV @ -130 dBm

<sup>2</sup> Dependent on aiding data connection speed and latency

<sup>3</sup> Demonstrated with a good active antenna

## Electrical data

Supply voltages	1.75 V – 2.0 V 2.5 V – 3.6 V
Digital I/O voltage level	1.65 V – 3.6 V
Power consumption	67 mW @ 1.8 V (continuous) 20 mW @ 1.8 V Power Save Mode (1 Hz)
Backup supply	Voltage range: 1.4 to 3.6V
RTC input	32.768 kHz (optional)
Antenna supervision	Short and open circuit detection supported with external circuit
Antenna type	Active and passive

## Interfaces

Serial interfaces	1 UART 1 USB V2.0 full speed 12 Mbit/s 1 DDC (I <sup>2</sup> C compliant) 1 SPI
Digital I/O	Configurable time pulse 2 EXTINT interrupt inputs 10 configuration pins

### Legal Notice

u-blox reserves all rights to this document and the information contained herein. Products, names, logos and designs described herein may in whole or in part be subject to intellectual property rights. Reproduction, use, modification or disclosure to third parties of this document or any part thereof without the express permission of u-blox is strictly prohibited.

The information contained herein is provided "as is". No warranty of any kind, either express or implied, is made in relation to the accuracy, reliability, fitness for a particular purpose or content of this document. This document may be revised by u-blox at any time. For most recent documents, please visit [www.u-blox.com](http://www.u-blox.com).

Copyright © 2011, u-blox AG

Specification applies to FW 7

## Package

UBX-G6010-NT:	45 Pin LGA (similar to QFN 42): 0.4 mm pitch, 5.0 x 6.0 x 1.1 mm
---------------	---

## Environmental data, quality & reliability

Operating temp.	-40°C to 85°C
Storage temp.	-40°C to 85°C
RoHS compliant (lead-free)	

## Support products

u-blox 6 Evaluation Kit: easy-to-use kit to get familiar with u-blox 6.

EVK-6H: u-blox6 Evaluation Kit with TCXO.

EVK-6P: u-blox6 Evaluation Kit with Crystal.

u-blox 6 Chipset Development Kit

CDK-6X: For information contact u-blox.

## Ordering information

UBX-G6010-NT	u-blox6 GPS chip, 45 Pin LGA
--------------	------------------------------

## Contact us

HQ Switzerland  
+41 44 722 7444  
[info@u-blox.com](mailto:info@u-blox.com)

China  
+86 10 68 133 545  
[info\\_cn@u-blox.com](mailto:info_cn@u-blox.com)

EMEA  
+41 44 722 7444  
[info@u-blox.com](mailto:info@u-blox.com)

Japan  
+81 3 5775 3850  
[info\\_jp@u-blox.com](mailto:info_jp@u-blox.com)

Americas  
+1 703 483 3180  
[info\\_us@u-blox.com](mailto:info_us@u-blox.com)

Korea  
+82 2 542 0861  
[info\\_kr@u-blox.com](mailto:info_kr@u-blox.com)

APAC – Singapore  
+65 6734 3811  
[info\\_ap@u-blox.com](mailto:info_ap@u-blox.com)

Taiwan  
+886 2 2657 1090  
[info\\_tw@u-blox.com](mailto:info_tw@u-blox.com)