

u-center v8.22

Public release notes

Abstract

Release notes containing general information, features, improvements, changes and known limitations for u-center v8.22.

www.u-blox.com

UBX-16017798 - R01

Document Information**Title** u-center v8.22**Subtitle****Document type** Release Notes**Document number** UBX-16017798**Revision and date** R01 26-Jul-2016**Document status** Production Information**Document status explanation**

Objective Specification Document contains target values. Revised and supplementary data will be published later.

Advance Information Document contains data based on early testing. Revised and supplementary data will be published later.

Early Production Information Document contains data from product verification. Revised and supplementary data may be published later.

Production Information Document contains the final product specification.

u-blox reserves all rights to this document and the information contained herein. Products, names, logos and designs described herein may in whole or in part be subject to intellectual property rights. Reproduction, use, modification or disclosure to third parties of this document or any part thereof without the express permission of u-blox is strictly prohibited.

The information contained herein is provided "as is" and u-blox assumes no liability for the use of the information. No warranty, either express or implied, is given, including but not limited to, with respect to the accuracy, correctness, reliability and fitness for a particular purpose of the information. This document may be revised by u-blox at any time. For most recent documents, please visit www.u-blox.com.
Copyright © 2016, u-blox AG.

u-blox® is a registered trademark of u-blox Holding AG in the EU and other countries.

Contents

| | |
|---|-----------|
| 1 General Information..... | 4 |
| 1.1 Released Files..... | 4 |
| 1.2 Version and Checksum of Files..... | 4 |
| 1.3 Revision Number..... | 4 |
| 1.4 Released Documentation..... | 4 |
| 2 Features..... | 5 |
| 2.1 Supported Microsoft Windows versions..... | 5 |
| 2.2 Supported Receiver Generations..... | 5 |
| 2.3 Supported Protocol Specification Version..... | 5 |
| 2.4 External hardware support..... | 5 |
| 2.5 Multiple GNSS AssistNow Service..... | 5 |
| 2.6 Debug Messages..... | 5 |
| 3 Improvements and Changes..... | 7 |
| 3.1 Version 8.22..... | 7 |
| 3.2 Version 8.21..... | 7 |
| 3.3 Version 8.20..... | 8 |
| 3.4 Version 8.19..... | 8 |
| 3.5 Version 8.18..... | 9 |
| 3.6 Version 8.17..... | 9 |
| 3.7 Version 8.16..... | 9 |
| 3.8 Version 8.15..... | 10 |
| 3.9 Version 8.14..... | 10 |
| 3.10 Version 8.13..... | 10 |
| 3.11 Version 8.12..... | 10 |
| 3.12 Version 8.11..... | 11 |
| 3.13 Version 8.10..... | 12 |
| 3.14 Version 8.01..... | 12 |
| 3.15 Version 8.00..... | 12 |
| 4 Known Limitations..... | 14 |
| 4.1 Known Issues..... | 14 |
| Contact..... | 15 |

1 General Information

The u-center GNSS evaluation software for automotive, mobile terminal and infrastructure applications provides a powerful tool for evaluation, performance analysis and configuration of u-blox GNSS receivers.

1.1 Released Files

The following table lists the files that have been released.

| File | Description |
|---|--|
| u-center_v8.22.exe | u-center installer incl. u-blox GNSS Standard Driver for Windows v1.2.0.8 and u-blox GNSS Sensor Device Driver for Windows v2.24 |
| u-center-v8.22_ReleaseNote_(UBX-16017798).pdf | Public release note |
| u-center_UserGuide_(UBX-13005250).pdf | User guide |

1.2 Version and Checksum of Files

The following table lists the versions and the checksums of the files inside the files as in [Chapter 1.1](#).

| File | Version | MD5 |
|--|---------|----------------------------------|
| u-blox GNSS Standard Driver for Windows | 1.2.0.8 | |
| u-blox GNSS Sensor Device Driver for Windows | 2.24 | |
| u-Center.exe | 8.22 | 96617059e7b94f1565fbd922caddde3e |
| flash.xml | 100111 | 69a65f50b211612e127243ec42a86427 |
| flash.xml_changelog.txt | | d43fe0b4d920615a61b4ae5bdc20db9 |
| flash.txt | 101098 | b49a4b5d33efa113737208e788cf3afc |
| NMEA.dll | 8.22 | 13a080de42d43aeb5ca1e618ff454786 |
| RTCM.dll | 8.22 | 6b981cd3205ab8824f4ebef6ab11da7c |
| UBX.dll | 8.22 | 6a0754c359af69b9bd1df37c48f03fd7 |

1.3 Revision Number

The u-center has the revision number **115363**.

1.4 Released Documentation

- Public Release Notes (UBX-16017798)
- u-center User Guide (UBX-13005250)

2 Features

2.1 Supported Microsoft Windows versions

u-center v8.22 will run on Microsoft Windows Vista up to and including Windows 10.

2.2 Supported Receiver Generations

u-center v8.22 can update the firmware of the following receiver generations:

- u-blox 5 with ROM 3.00, ROM 4.00, ROM 5.00
- u-blox 6 with ROM 6.00, ROM 6.02, ROM 7.03
- u-blox 7 with ROM 0.10, ROM 0.11, ROM 0.14, ROM 1.00
- u-blox 8/M8 with ROM 0.21, ROM 0.22, ROM 2.01, ROM 3.01



Antaris based receivers are **no longer** supported.



u-blox 5 receivers support is end of life and will be removed in one of the next versions.

2.3 Supported Protocol Specification Version

u-center v8.22 supports the u-blox protocol specification from version 10.00 up to and including version 22.00.

2.4 External hardware support

The following external hardware is supported to interface with the receiver:

| Interface | Device | DLL version |
|-----------|--|---|
| DDC/I2C | Totalphase Aardvark I2C/SPI Host Adapter | aardvark.dll v5.15 for Windows 32-bit |
| DDC/I2C | Diolan U2C-12 USB-I2C/SPI/GPIO Adapter | i2cbrdg.dll v1.0.0.9 for Windows 32-bit |
| SPI | Totalphase Aardvark I2C/SPI Host Adapter | aardvark.dll v5.15 for Windows 32-bit |
| SPI | Totalphase Cheetah SPI Host Adapter | aardvark.dll v5.15 for Windows 32-bit |
| SPI | Diolan U2C-12 USB-I2C/SPI/GPIO Adapter | i2cbrdg.dll v1.0.0.9 for Windows 32-bit |

2.5 Multiple GNSS AssistNow Service

u-center v8.22 includes the multiple GNSS AssistNow Service (libMGA) version 1.05.

2.6 Debug Messages

The following messages will be enabled or polled when pressing the "Debug Messages" button:

- Any UBX-INF
- UBX-ESF-MEAS
- UBX-ESF-STATUS
- UBX-MON-MSGPP
- UBX-NAV-CLOCK
- UBX-NAV-PVT
- UBX-NAV-SOL
- UBX-NAV-SVINFO
- UBX-RXM-SVSI (every 30 seconds)
- UBX-MON-HW (polled)
- UBX-MON-EXCEPT (polled)

- and additional u-blox debug messages

3 Improvements and Changes

3.1 Version 8.22

- New message UBX-RXM-RTCM
- New message UBX-CFG-REMFS
- New message UBX-NAV-HPPOSECEF
- New message UBX-NAV-HPPOSLLH
- Update of UBX-ACK/NAK: Bug fixes
- Update of UBX-CFG-TMODE3: Cosmetic UI improvements
- Update of UBX-ESF-STATUS: Speed flag now set
- Update of UBX-CFG-NMEA: Added high precision flag
- Update of UBX-MON-MSGPP: Cosmetic UI improvements
- Update of UBX-MON-SENI: Cosmetic UI improvements
- Update of UBX-NAV-SOL: Updated extraction of revision bits
- Update of UBX-NAV-PVT: Cosmetic UI improvements, updated extraction of revision bits
- Update of UBX-NAV-RELPOSNED: Reporting additional receiver information to u-center's database
- Update of UBX-CFG-ESFDWT: Cosmetic UI changes
- Update of UBX-CFG-ESFGWT: Cosmetic UI changes
- Update to UBX-NAV-ATT: Reporting additional receiver information to u-center's database
- UBX-CFG-HPGROV renamed to UBX-CFG-DGNSS, plus cosmetic UI changes
- New RTCM3 parser
- New option to reset to default colors in preference property pages
- New access tokens preferences property page
- Map view overhauled and upgraded to compensate for the loss of Google Earth view
- Added Google maps API key entry to access tokens property page
- Various minor cosmetic updates

3.2 Version 8.21

- Support for ADR4.00
- Support for HPG1.00
- Support for TIM1.10
- Support for UDR1.00
- New message UBX-CFG-HNR
- New message UBX-CFG-TMODE3
- New message UBX-NAV-RELPOSNED
- New message UBX-RXM-RLM
- Update of UBX-CFG-GNSS: Layout changes
- Update of UBX-CFG-MSG: RTCM messages 1005, 1077, and 1087 added
- Update of UBX-CFG-NAV5: Signal attenuation feature is public
- Update of UBX-CFG-NAVX5: Flag `useAdr` is public
- Update of UBX-CFG-PM2: Message version selector visible
- Update of UBX-CFG-PMS: Aggressive 2Hz option is public
- Update of UBX-CFG-PRT: RTCM3 added
- Update of UBX-CFG-SBAS: Flag `enable` and `maxSbas` marked deprecated for u-blox 8
- Update of UBX-CFG-TP5: Rename of `Invert pulse polarity` to `Rising Edge of TOS`
- Update of UBX-NAV-PVT: Flag `carrSoln` is public

- Added epoch detection options
- Added PC time option to console views
- Added DGNSS interface option
- Connected receiver can be recognized based on the boot screen
- Support of new signal IDs in various messages
- Support of legacy aiding (online and offline) with MGA servers
- Rename of carrier phase to carrier range
- Fixed warning when database is cleared for UBX-CFG-NMEA
- Fixed auto-poll for UBX-CFG-GEOFENCE
- Update of 2D and 3D accuracy data view: Allow smaller values to display increased accuracy
- Update of status bar: Tooltips, DGNSS and receiver power state information added
- General harmonization with Protocol Specification
- Log file player speed adaptations and clarification. Based on messages/second.
- Default file name changed for retrieved log file
- Update of tinyXML2 library to version bb4d246

3.3 Version 8.20

- Fix bug in USB alternate update method for firmware update with ROM 3.01

3.4 Version 8.19

- New message UBX-CFG-DYNSEED
- New message UBX-CFG-FIXSEED
- New message UBX-CFG-GEOFENCE
- New message UBX-NAV-EOE
- New message UBX-NAV-GEOFENCE
- New message UBX-NAV-TIMEGAL
- New message UBX-RXM-IMES
- New message UBX-RXM-RLM
- New message UBX-SEC-SIGN
- New message UBX-SEC-UNIQID
- Support of new message version for UBX-RXM-PMREQ
- Support of new message version for UBX-RXM-RAWX
- Support of new message version for UBX-RXM-SFRBX
- Add wrist model to UBX-CFG-NAV5
- Update constrains in UBX-CFG-RATE
- Add Galileo to UBX-CFG-TP5
- Add Galileo to UBX-MON-GNSS
- Add geofence pin to UBX-MON-HW
- Add spoofing detect state to UBX-NAV-STATUS
- Add unknown source of leap seconds to UBX-NAV-TIMELS
- Add wake up sources to UBX-RXM-PMREQ
- Support from ROM 3.01
- Remove of Google Earth view
- Support of legacy aiding in Multiple GNSS AssistNow Online
- Support of new GNSS in Multiple GNSS AssistNow
- u-center can now connect to Location and Sensor API of Windows 7 onwards
- Fix Google Earth Server functionality
- Using new code signing certificate

- Increase internal resolution of latitude and longitude
- Decouple the epoch detection for NAV and HNR messages
- Color selection in Preferences is now public
- Main window title now shows either connection name or log file name
- Enabled more than 2GB of memory to be used on 64 bit versions of Windows
- Update database of known firmwares
- Various cosmetic fixes (typos, unicode issues, user interface elements positions and sizes)
- Various stability fixes

3.5 Version 8.18

- Updates to UBX-CFG-DAT
- Updates to UBX-CFG-ESFGWT
- Updates to UBX-CFG-NAV5
- Updates to UBX-CFG-PM2
- Updates to UBX-CFG-RXM
- Updates to UBX-MGA messages
- Updates to UBX-NAV-PVT
- Updates to UBX-RXM-PMREQ
- Updates to UBX-RXM-RAWX
- Updates to UBX-TIM-SMEAS
- Fixed miscellaneous minor bugs
- Added auto scale feature on deviation map by double clicking in deviation map view
- Fixed issues with displaying COG in the Table View
- Message view's hex area not displayed by default
- Improvements in BeiDou support

3.6 Version 8.17

- Updates to UBX-CFG-GNSS
- Updates to UBX-CFG-ESFGWT
- Updates to UBX-ESF-STATUS
- Updates to UBX-MON-HW
- Updates to UBX-CFG-NAV5
- Updates to NMEA-PUBX
- Updates to UBX-INF
- Updates to UBX-RXM-RAW
- Updates to UBX-CFG-ANT
- Updates to Dump Receiver Diagnostics
- Improved Binary view window display speed
- Miscellaneous memory leak fixed
- u-center acting as a Google Earth server now fixed (unicode issue)
- Table, Chart and Histogram views now have improved property search facility

3.7 Version 8.16

- Sky View shows additional satellite systems (Glonass, Beidou, Galileo)
- Satellite names in the various views (and flags in the satellite view) are now correct

3.8 Version 8.15

- AssistNow Online fixed (reported wrong username/password)

3.9 Version 8.14

- Update of UBX-TIM-TOS handling: allow enabling/disabling
- Update of UBX-ESF-STATUS: add error status field
- Update of UBX-TIM-VCOCAL: make command 'STOP' public
- Update of UBX-CFG-MSG list: matching protocol specification
- Update of UBX-CFG-RST: Allow 'User Defined' option, make SFDR and TCT public
- Update of UBX-MON-EXCEPT
- Add keyboard shortcut for firmware update dialog (Ctrl-u)
- Add toolbar icon for firmware update dialog
- Add status text for 'Sky View': azimuth and elevation
- Make configuration of antenna supervisor pins public
- Negative Course over Ground values can now plotted in the ChartView
- Google Earth view saves KML file as ASCII text
- Default name for exporting as KML file based on time and date
- Save GNSS configuration to file fixed
- Switch to UNICODE
- Update of shortcuts
- Update TotalPhase Cheetah driver to v3.08
- Rename of database entry 'TTAG (from ITOW)' to iTOW (according to protocol specification)
- Fix of GPS time from UBX-NAV-TIMEBDS
- Tooltip delay set to 200ms
- Minor fixes

3.10 Version 8.13

- Support of messages for M8L products
- Update of graphs for UBX-ESF-MEAS
- Visual improvements when using several monitors
- Update of statistic view (search and sort function)
- Fix problem with empty entries in table view
- Add option to hide tree and HEX view
- Add File transfer dialog
- Update of deviation map
- Show IRNSS flags

3.11 Version 8.12

- Update UBX-CFG-PM2
- Update UBX-CFG-TXSLOT
- Update UBX-NAV-TIMEUTC
- Update UBX-TIM-TP
- Update UBX-TIM-TM2
- Update UBX-TIM-VCOCAL
- Update UBX-ESF-MON
- Update UBX-MON-EXCEPT
- Update UBX-MON-HW

- Add support for LEA-M8T messages and firmware
- Add support for UTC standard (NTSC)
- Add Qi to database
- Add more EKF fields to database
- Add 2D error ellipse to database
- Odometer fields are now public in database
- Improve speed for deleting database
- Workspace and view configuration format changed
- Fix mismatch between binary console and message view
- Fix problem when saving map view
- Add extra line in consoles to separate data packets
- Add tooltip for satellite level view
- Add direction indicator of messages
- Add possibility to filter message tree by protocol specification versions
- Fix possible memory leak problems

3.12 Version 8.11

- Update of UBX-CFG-SMGR
- Update of UBX-CFG-DOSC
- Update of UBX-CFG-SMGR
- Update of UBX-CFG-ESRC
- Update of UBX-CFG-TP5
- Update of UBX-NAV-STATUS
- Update of UBX-TIM-TOS
- Add UBX-MON-SMGR, UBX-TIM-SMEAS and UBX-TIM-FCHG to periodic poll messages
- Set UBX-CFG-DOSC to public
- Set UBX-CFG-ESRC to public
- Set UBX-CFG-SMGR to public
- Set UBX-MON-SMGR to public
- Set UBX-TIM-DOSC to public
- Set UBX-TIM-FCHG to public
- Set UBX-TIM-SMEAS to public
- Set UBX-TIM-TOS to public
- Set UBX-TIM-VCOCAL to public
- Set UBX-TIM-VCOFF to public
- Link to User's Guide in the help menu
- Fix problem with connection tool tip
- Fix problem with Google Earth plug-in when altitude = null
- Add option to align time-pulse to BeiDou or GLONASS time in UBX-CFG-TP5 (FTS product only)
- Fix problem with x axes label
- Adding the option to continuously update the receiver with MGA data
- Adding pop-up message when connection to receiver fails
- Improve resolution of position and velocity data storage and plots
- Update of MGA online dialog
- NMEA strict 82 characters only applicable for UBX-CFG-NMEA-DATA2
- Fix possible memory leak problem for external interface devices

3.13 Version 8.10

- Update of UBX-MON-GNSS dialog
- Update of UBX-CFG-NAV5 dialog (added UTC standard configuration)
- Update of UBX-CFG-PRT dialog (renaming Pin to PIO)
- Set UBX-MGA-QZSS to public
- Set UBX-UPD-SOS to public
- Set UBX-LOG-RETRIEVE, UBX-LOG-RETRIEVEPOS,UBX-LOG-RETRIEVESTRING, UBX-LOG-RETRIEVEPOSEXTRA to public
- Rename of UBX-NAV-ODORESET to UBX-NAV-RESETO
- Make UDP and TCP client public again
- Fix localisation problem
- Fix problem when saving a log file from a network connection (invalid characters)
- Add menu option for AssistNow online and offline
- Add support for tool tips in message views
- Remove Antaris support

3.14 Version 8.01

- Update of UBX-CFG-NAVX5 dialog
- Update of UBX-NAV-AOPSTATUS dialog
- Update of UBX-NAV-HNR support
- Update of UBX-NAV-SAT dialog: ANO/AOP was switched
- Update of UBX-RXM-SFRBX dialog
- Support for UBX-EST-MON version 2
- Support for ROM 2.01
- Firmware update mechanism improvements (file system, new settings)
- Added Timemark 1 and 2 edge information and time pulse quantization error to public chart usage
- Update of network connection menu
- Added command line option to connect to receiver
- Fix problem with 'Dump receiver diagnostic' in u-center
- Update of help dialog
- Update of database export to Google Maps HTML file (fix stack overflow in IE8)
- MGA dialog:
 - o Button in u-center to request a token
- Support for 50/250bps IMES
- ADR updates:
 - o Sensor-to-vehicle frame misalignment angle
 - o Yaw misalignment angle updates

3.15 Version 8.00

- Add UBX-CFG-HNR and UBX-NAV-HNR
- Fix UBX-CFG-PRT dialog: make 'Extended time-out' public
- Update of UBX-CFG-NMEA dialog
- Update of UBX-ESF-MEAS dialog
- Update of UBX-CFG-MSG dialog
- Update of NMEA-GSV
- NMEA-GSA proper handling of several messages (multi GNSS support)
- libMGA: minor fixes
- MGA dialog

- o Set smart flow control as default
- o Fix crash
- o Add UBX-MGA-INI-EOP to known messages
- o Make download button the default
- Add 3D button and support in Google Earth View
- Add zooming feature for Chart view (Ctrl + mouse wheel = zoom in/out, left mouse double click = fit)
- Reset TTFF when receiver is cold/warm/hot started
- Renaming

4 Known Limitations

4.1 Known Issues

- Enumerating the ports on a computer with many ports can take long
- Using protocol filter with silent / no receiver results in empty message tree

Contact

For complete contact information visit us at www.u-blox.com

u-blox Offices

North, Central and South America

u-blox America, Inc.

Phone: +1 703 483 3180
E-mail: info_us@u-blox.com

Regional Office West Coast:

Phone: +1 408 573 3640
E-mail: info_us@u-blox.com

Technical Support:

Phone: +1 703 483 3185
E-mail: support_us@u-blox.com

Headquarters Europe, Middle East, Africa

u-blox AG

Phone: +41 44 722 74 44
E-mail: info@u-blox.com
Support: support@u-blox.com

Asia, Australia, Pacific

u-blox Singapore Pte. Ltd.

Phone: +65 6734 3811
E-mail: info_ap@u-blox.com
Support: support_ap@u-blox.com

Regional Office Australia:

Phone: +61 2 8448 2016
E-mail: info_anz@u-blox.com
Support: support_ap@u-blox.com

Regional Office China (Beijing):

Phone: +86 10 68 133 545
E-mail: info_cn@u-blox.com
Support: support_cn@u-blox.com

Regional Office China (Chongqing):

Phone: +86 23 6815 1588
E-mail: info_cn@u-blox.com
Support: support_cn@u-blox.com

Regional Office China (Shanghai):

Phone: +86 21 6090 4832
E-mail: info_cn@u-blox.com
Support: support_cn@u-blox.com

Regional Office China (Shenzhen):

Phone: +86 755 8627 1083
E-mail: info_cn@u-blox.com
Support: support_cn@u-blox.com

Regional Office India:

Phone: +91 80 4050 9200
E-mail: info_in@u-blox.com
Support: support_in@u-blox.com

Regional Office Japan (Osaka):

Phone: +81 6 6941 3660
E-mail: info_jp@u-blox.com
Support: support_jp@u-blox.com

Regional Office Japan (Tokyo):

Phone: +81 3 5775 3850
E-mail: info_jp@u-blox.com
Support: support_jp@u-blox.com

Regional Office Korea:

Phone: +82 2 542 0861
E-mail: info_kr@u-blox.com
Support: support_kr@u-blox.com

Regional Office Taiwan:

Phone: +886 2 2657 1090
E-mail: info_tw@u-blox.com
Support: support_tw@u-blox.com